

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: BRUSHABLE SEAM SEALER**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Sealant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
LKQ Coatings
Newberry House, Michigan Drive
Tongwell, Milton Keynes
MK15 8HQ
T: 01908 611117
E: optimaproducts@lkqcoatings.com
- **Further information obtainable from:** Product safety Department
- **1.4 Emergency telephone number:** Tel: 01908 611117

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02

GHS07

GHS08

- **Signal word** Warning
- **Hazard-determining components of labelling:**
Xylene, mixed isomers, pure
- **Hazard statements**
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

(Contd. on page 2)

Trade name: BRUSHABLE SEAM SEALER

(Contd. of page 1)

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P243 Take precautionary measures against static discharge.
- P280 Wear protective gloves/protective clothing/eye protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with additions.

Dangerous components:

CAS: 1330-20-7	Xylene, mixed isomers, pure	25-<50%
EINECS: 215-535-7	⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304;	
Reg.nr.: 01-2119488216-32	⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

5.3 Advice for firefighters

· **Protective equipment:** Mount respiratory protective device.

(Contd. on page 3)

Trade name: BRUSHABLE SEAM SEALER

(Contd. of page 2)

· **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin, eyes and clothes.

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling** Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep container tightly sealed.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 1330-20-7 Xylene, mixed isomers, pure

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

· **Regulatory information** WEL: EH40/2011

· DNELs

CAS: 1330-20-7 Xylene, mixed isomers, pure

Dermal Long-term - systemic effects, worker

180 mg/kg bw/day (Worker)

Long-term - systemic effects, general population

108 mg/kg bw/day (General population)

Inhalative Acute - Local effects, worker

289 mg/m³ (Worker)

Long-term - systemic effects, worker

77 mg/m³ (Worker)

Acute - systemic effects, general population

174 mg/m³ (General Population)

Acute - systemic effects, worker

289 mg/m³ (Worker)

Acute - local effects, general population

174 mg/m³ (General Population)

(Contd. on page 4)

Trade name: BRUSHABLE SEAM SEALER

(Contd. of page 3)

	Long-term - systemic effects, general population	14.8 mg/m ³ (General Population)
--	--	---

· **PNECs**

CAS: 1330-20-7 Xylene, mixed isomers, pure

Aquatic compartment - freshwater	0.327 mg/L (not specified)
Aquatic compartment - marine water	0.327 mg/L (not specified)
Aquatic compartment - sediment in freshwater	12.46 mg/kg sed dw (not specified)
Aquatic compartment - sediment in marine water	12.46 mg/kg sed dw (not specified)
Terrestrial compartment - soil	2.31 mg/kg dw (not specified)
Sewage treatment plant	6.58 mg/L (not specified)

· **Ingredients with biological limit values:**

CAS: 1330-20-7 Xylene, mixed isomers, pure

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· **Regulatory information** BMGV: EH40/2011

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**



Filter A

· **Protection of hands:**



Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Fluorocarbon rubber (Viton)

Recommended thickness of the material: $\geq 0,12$ mm

· **Penetration time of glove material**

> 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

(Contd. on page 5)

Trade name: BRUSHABLE SEAM SEALER

· **Body protection:** Use protective suit.

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:	Pasty
· Colour:	Grey
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· Change in condition

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	136-145 °C

· **Flash point:** 23-29 °C (DIN 53213)

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 500 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

· Lower:	1.0 Vol %
· Upper:	7.1 Vol %

· **Vapour pressure At 20 °C:** 10 hPa

· **Vapour pressure At 50 °C:** 20 hPa

· **Density At 20 °C:** 1.22 g/cm³ (DIN 51757)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.

· Viscosity:

· **Dynamic At 20 °C:** 240000 mPas

· **Kinematic:** Not determined.

· Solvent content:

· **Organic solvents:** 33.0 %

· **Solids content:** 66.8 % (DIN 53216)

· **9.2 Other information** No further relevant information available.

· **VOC (EU):** 32.97 %

· **VOC (EU):** 402.2 g/l

· **VOCV:** 32.97 %

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

(Contd. on page 6)

Trade name: BRUSHABLE SEAM SEALER

(Contd. of page 5)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Dermal	LD50	6270 mg/kg (RABBIT)
--------	------	---------------------

CAS: 1330-20-7 Xylene, mixed isomers, pure

Oral	LD50	8700 mg/kg (RAT)
Dermal	LD50	2000 mg/kg (RABBIT)
Inhalative	LC50/4 h	6350 mg/l (RAT)
	LC50/24 h	100-1000 mg/l (DAPHNIA MAGNA)
	LC50/96 h	1-10 mg/l (Fish)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:** No further relevant information available.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 1330-20-7 Xylene, mixed isomers, pure

EC50/48 h	1-10 mg/l (DAPHNIA MAGNA)
EC50/72 h	1-10 mg/l (ALGAE)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 7)

Trade name: BRUSHABLE SEAM SEALER

(Contd. of page 6)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Dispose of as dangerous waste.

- **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP 3	Flammable
HP 4	Irritant - skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 6	Acute Toxicity

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR/RID/ADN, ADN** Void
- **IMDG, IATA** UN1263

- **14.2 UN proper shipping name**
- **ADR/RID/ADN, ADN** Void
- **IMDG, IATA** PAINT

- **14.3 Transport hazard class(es)**
- **ADR/RID/ADN, ADN**
- **Class** Void

- **IMDG, IATA**



- **Class** 3 Flammable liquids.
- **Label** 3

- **14.4 Packing group**
- **ADR/RID/ADN** Void
- **IMDG, IATA** III

- **14.5 Environmental hazards:**
- **Marine pollutant:** No

- **14.6 Special precautions for user** Not applicable.
- **EMS Number:** F-E,S-E
- **Stowage Category** A

(Contd. on page 8)

Trade name: BRUSHABLE SEAM SEALER

(Contd. of page 7)

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	Transport classification ADR/IMDG is based on packaging >30ltr(IMDG), <450ltr(ADR). For other packaging units different classification can apply.
· ADR/RID/ADN · Remarks:	Transport is in line with the remarks under 2.2.3.1.5 of the ADR code till a volume of 450 ltr. If ADR > 450 ltr than class 3, packaging group III must be applied with accessory UN-number.
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ) · Remarks:	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Transport is in line with the remarks under 2.3.2.5 of the IMDG code till a volume of 30 ltr. If IMDG > 30 ltr than class 3, packaging group III must be applied.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Warning
- **Hazard-determining components of labelling:**
Xylene, mixed isomers, pure
- **Hazard statements**
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/protective clothing/eye protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

(Contd. on page 9)

Trade name: BRUSHABLE SEAM SEALER

(Contd. of page 8)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	33.0

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing SDS:** Product safety department.

· **Contact:** optimaproducts@lkqcoatings.com

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**