

OPT.BSX1

# OPTIMA 1L BODY SCHUTZ

## Technical Data Sheet

### PRODUCT DESCRIPTION

Optima Body Shutz is a durable, thixotropic, fast drying, anti-corrosion coating based on bitumen. The product has excellent sound deadening effects and offers a durable protection to the chassis of for instance cars, trucks and coaches. After drying remains a tough, adhesive film resistant against various climates and gravel.

### FEATURES AND BENEFITS:

- Proven durability
- Fast drying
- Sound deadening properties
- Body Shutz is also available in a 500ml aerosol can

### APPLICATION

Body Shutz is applied as an anti-corrosion protection for instance for chassis, wheel-housings and side- skirts of cars, trucks and coaches in:

- Automotive industry
- Coach work industry
- Camper & caravan industry, e.g. coating and/or repair of the underside of the plywood floor panel
- Garages, work shops
- Bus construction;
- Carriage and container construction.

### USER INSTRUCTIONS:

Shake before use.

The surfaces to be treated must be clean, dry, rust-, dust- and grease free.

Optima Body Shutz can be applied with light airless equipment, but also by means of an air-line fed gun with an air-pressure of 3-6 bar.

Optimum spraying distance is about 30 cm.

Spray the surface with Body Shutz until the desired layer thickness is reached.

If thicker layers are wanted, it is to be recommended to dry the layers in between.

Contaminated surfaces and equipment can be simply cleaned with solvents.

**PPE:** Always wear appropriate PPE in line with your Risk assessment & COSHH assessment policy for using this product

**HEALTH & SAFETY:** For Health and Safety information please refer to the material Safety Data Sheet (SDS).

**STORAGE:** The product may not be stored under +10°C and above +30°C  
The packaging must be protected from direct sunlight and heat.

**SHELF LIFE:** 2 years in the unopened original packaging.

**PACKAGING:** 1L Can

optima

OPT.BSX1 TDS 2019

**DISCLAIMER**

All statements, technical information and recommendations are based on tests we believe to be reliable but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.

**For Professional use only**

These products are for professional use only and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose.

**Optima Products**, Newberry House, Michigan Drive, Tongwell,  
Milton Keynes, Buckinghamshire, MK15 8HQ  
**Tel:** 01908 611117 **Email:** [Optimaproducts@LKQCoatings.com](mailto:Optimaproducts@LKQCoatings.com)