

OPT.CWAX500A

OPTIMA 500ML CAVITY WAX AMBER AEROSOL

Technical Data Sheet

PRODUCT DESCRIPTION

Optima Cavity Wax is an amber coloured thin liquid anti-corrosion coating for the protection of cavity areas in cars, trucks, coaches and other objects or places where a rust preventative surface is needed.

The product is water-repellent and has very good penetrating properties and a "self-healing" effect. After drying remains a slightly sticky wax coating which has a good temperature resistance up to +160 , so it can be used for example in engine compartments.

FEATURES AND BENEFITS:

- Good protection of cavity areas
- High temperature resistance
- Self-healing properties
- Optimal penetrating power
- Low odour

APPLICATION

Optima Cavity Wax is applied as an anti-corrosion coating to protect cavity areas like doors, bonnet, cross members, reinforcements etc. in cars, trucks and coaches or as a universal anti corrosion product for machine parts and other tools. They also are excellent universal applicable anti corrosion products in:

- Automotive industry
- Coach works
- Bus & coach construction
- Trailer construction
- Metal industry
- Ship construction
- Garages, workshops
- Body repair shops

USER INSTRUCTIONS:

Shake before use.

The surfaces to be treated must be clean, dry, rust-, dust- and grease free

ADHESION: In general cavity waxes adhere very well (without special pretreatment) on a wide range of clean, dry, dust- and grease free metal surfaces. It is always advisable to perform an adhesion test on the materials involved.

PPE: Always wear appropriate PPE in line with your Risk assessment & COSHH assessment policy for using this product

HEALTH & SAFETY: For Health and Safety information please refer to the material Safety Data Sheet (SDS).

STORAGE: The product may not be stored under +10°C and above +30°C
The packaging must be protected from direct sunlight and heat.

SHELF LIFE: 2 years in the unopened original packaging.

optima

OPT.CWAX500A TDS 2019

PACKAGING: 500ml Aerosol can

DISCLAIMER

All statements, technical information and recommendations are based on tests we believe to be reliable but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.

For Professional use only

These products are for professional use only and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose.

Optima Products, Newberry House, Michigan Drive, Tongwell,
Milton Keynes, Buckinghamshire, MK15 8HQ
Tel: 01908 611117 **Email:** Optimaproducts@LKQCoatings.com

optima

OPT.CWAX500A TDS 2019