




## Double Sided Mounting Tape Technical Data Sheet

### PRODUCT DESCRIPTION

Optima Double Sided Mounting Tape has a high tack permanent adhesive with excellent ageing and weather resistant properties for automotive emblems, decals, mouldings and mirror fixings. The product also has a good resistance to solvents, chemicals, UV and heat.

### PRODUCT CONSTRUCTION



### SHELF LIFE

One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

### PHYSICAL PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Carrier	High Performance PE Foam (96kg/m <sup>3</sup> ) Black
Liner	Green Polyolefin
Adhesive	Acrylic (Solvent Based)
Thickness	0.8mm (+/- 0.05mm)
Width	6mm, 9mm, 12mm, 25mm and 50mm (+/- 1mm)
Length	10m (+/- 0.1m)

### PERFORMANCE PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Peel Adhesion	PSTC-3 1.8kg/25mm
Shear Strength	PSTC-7 over 24 hours with 2kg on 25mm x 25mm at 23°C
Tensile Strength	Over 45kgs/25mm x 25mm
Heat Resistance	PSTC-9 over 24 hours with 0.5kg on 25mm x 25mm at 80°C
Tack	J. Dow Number 20

