



OPT.LT

optima

Logo Tape

Technical Data Sheet

PRODUCT DESCRIPTION

Optima Logo Tape is purposely designed for recovering logos and emblems from all types of vehicles – reducing costs and speeding up the reclaim process. The product is also ideal for positioning parts before final fixing or for fixing decorative and promotional items.

PRODUCT CONSTRUCTION



SHELF LIFE

One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Carrier	Silicone Release Liner
Liner	Double Sided Liner
Adhesive	High Tack Acrylic (Solvent Based)
Thickness	0.04mm (+/- 0.05mm) Clear only.
Total	Thickness 0.167mm (+/- 0.05mm)
Width	50mm (+/- 1mm)
Length	300mm (+/- 0.1mm)

PERFORMANCE PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Adhesion to Steel	ASTM D 8.75N/10cm
Service Temperature	-40°C to 170°C
Application Temperature	-10°C to 35°C



Optima Products, Newberry House, Michigan Drive, Tongwell, Milton Keynes, Buckinghamshire, MK15 8HQ
Tel: 01908 611117 Email: Optimaproducts@LKQCoatings.com