OPT.NWP Non-Woven Pads Technical Data Sheet

optima

PRODUCT DESCRIPTION

The Optima Non-woven Pad is a flexible, three-dimensional fibre sanding material. That is easy to use on profiled surfaces and produces an excellent finish. It is ideal for matting of surfaces and creates an excellent base for the next lacquer layer.

INSTRUCTIONS FOR USE

- Always store the product in a dry environment, ideally 10°C to 25°C
- Always wear the relevant PPE safety equipment
- Take the Optima Non-Woven pad and abrade the panel
- Can be used wet with a water applicator and matting pastes if required

PRODUCT HIGHLIGHTS

- · Good sanding and durability
- Pre-cut in a pack of 20
- · Good for accessing the difficult to reach areas
- Can be used wet or dry

PRODUCT DETAILS

Sizes Available:	152mm x 229mm
Grits:	Red (Very Fine) – P360
	Grey (Ultra Fine) – P1500

TECHNICAL SPECIFICATIONS

Bonding:	Resin
Grain:	Aluminium oxide (Very Fine)/
	Silicon carbide (ULTRA FINE)
Colour:	Red & Dark Grey
Grit Range:	P360 & P1500
Backing:	Non-woven

DISCLAIMER

All statements, technical information and recommendations are based on tests we believe to be reliable but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.



Optima Products, Newberry House, Michigan Drive, Tongwell, Milton Keynes, Buckinghamshire, MK15 8HQ Tel: 01908 611117 Email: Optimaproducts@LKQCoatings.com