



OPT.PFR

Perforated Foam Roll Technical Data Sheet

optima

PRODUCT DESCRIPTION

The Optima Perforated Foam Roll has been developed for sanding profiled surfaces and irregular, difficult-to-reach details by hand. Especially useful within the automotive industry and bodyshops. The foam base is grip-friendly and applies pressure evenly, which reduces the risk of sanding through the surface. The special stearate coating prevents clogging. It is also suitable for both dry and wet sanding.

INSTRUCTIONS FOR USE

- Always store the product in a dry environment, ideally 10°C to 25°C
- Always wear the relevant PPE safety equipment
- Tear off sheets as required and sand the areas by hand until desired result is achieved

PRODUCT HIGHLIGHTS

- Aluminium oxide grain for optimum sanding and durability.
- Consistent grain distribution provides an even and consistent scratch pattern
- A-Latex paper backing is highly resistant to tearing
- Very Flexible
- Pigment free stearate coating prevents colour transfer and minimises clogging
- Suitable for wet or dry sanding

PRODUCT DETAILS

Sizes Available: 115mm x 25mtrs
Grits: P180, P240, P320, P400, P500,
P600, P800 & P1000

TECHNICAL SPECIFICATIONS

Bonding:	Resin over resin
Grain:	Aluminium oxide
Colour:	Gold
Grit Range:	P180 – P1000
Backing:	A-latex paper, PE foam

DISCLAIMER

All statements, technical information and recommendations are based on tests we believe to be reliable but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.

