



Perforated Trim Masking Tape Material Safety Data Sheet

1. CHEMICAL PRODUCT

Product Name	Perforated Trim Masking Tape
Classification of Product	Specialist Masking Tape
Revision Date	2015. 09. 16

2. COMPOSITION

INGREDIENT	%
Saturated Paper Backing	45-55
Pressure sensitive adhesive	25-35
Polyester film	20

3. HEALTH HAZARD DATA

No adverse health effects are expected from the use of this product.

4. EMERGENCY & FIRST AID PROCEDURE

Eye Contact	N/A
Skin Contact	N/A
Inhalation	N/A
Ingestion	Drink two glasses of water. Call a medical doctor.

5. FIRE & EXPLOSION

Suitable Extinguishing Media	Water, water spray, carbon dioxide, dry chemical
Hazardous Decomposition	Carbon monoxide, carbon dioxide and trace amounts of HCN may evolve during burning.
Fire-Fighting Procedures	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.
Special Instructions	N/A

6. ACCIDENTAL RELEASE MEASURES

Protection of Humans	Avoid dust formation. Avoid breathing vapours, mist or gas.
----------------------	---

7. HANDLING & STORAGE

Safe handling	This product does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.
Storage	Keep dry and cool (below 25°C) and away from direct sunlight for quality.

8. PERSONAL PROTECTION & EXPOSURE CONTROLS

Engineering Management	Not applicable.
Respiratory protection	Not applicable.
Eye protection	Not applicable.
Hand protection	Not applicable.

9. PHYSICAL & CHEMICAL CHARACTERISTICS

Appearance	Roll
Odour	Slight
Boiling point	No data
Vapour pressure	No data
Melting point	No data
Solubility	No data
Relative density	No data
Viscosity	No data





Perforated Trim Masking Tape Material Safety Data Sheet

10. STABILITY & REACTIVITY

Stability	Stable
Material to avoid	Strong acids or strong oxidizing agents
Conditions to avoid	No data
Hazardous decomposition products	Thermal decomposition will produce mainly CO ₂ , some CO and various hydrocarbons.
Hazardous polymerization	Will not occur

11. TOXICITY DATA

Effect on eye	May cause eye irritation.
Effect on skin	May be harmful if absorbed through skin. May cause skin irritation.
Inhalation	May be harmful if inhaled. May cause respiratory tract irritation.
Ingestion	May be harmful if swallowed.

12. ENVIRONMENTAL DATA

Not determined.

13. DISPOSAL PROCEDURE

Disposal of waste product should conform to the state and local regulations management law.

14. TRANSPORT DATA

UN NO.	No data.
International classification	Not applicable.

15. REGULATION

Domestic laws	Industry safety health law: toxicological material Toxicological chemical material control law: toxicological
Other foreign law	None.
OSHA Hazard communication	None.

16. OTHER INFORMATION

REGULATORY INFORMATION:

The following UK Regulations as amended may affect the product as supplied:

- The Chemicals (Hazard Information and Packaging for supply) Regulations, as amended.
- The Carriage of Dangerous Goods (Classification, Packaging and Labelling) and use of Transportable Pressure Receptacles Regulations 1996, as amended.
- Carriage of Dangerous Goods by Road Regulations, 1996, as amended.
- The Petroleum (Consolidation) Act 1928.
- The Control of Substances Hazardous to Health Regulations 1999 as amended.
- The Special Waste Regulations 1996, as amended.
- The Environmental Protection Act, 1990
- The Health and Safety at Work Act, 1974.

INTENDED USE OF PRODUCT:

Protects rubber trims and bodyside mouldings during spraying. Perforated for easy tear off and flexible to follow contours and tight curves.

The information on this Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law).

The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials.

For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

