



OPT.RT

optima

Refit Tape

Technical Data Sheet

PRODUCT DESCRIPTION

Optima Refit Tape is a permanent adhesive transfer tape with an instant, aggressive bond and good humidity resistance, even on difficult to stick surfaces. UV and chemical resistant.

PRODUCT CONSTRUCTION



SHELF LIFE

One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Carrier	Silicone Release Paper
Liner	Double Sided Liner
Adhesive	High Tack Acrylic (Solvent Based)
Thickness	0.05mm (+/- 0.05mm)
Total Thickness	0.125mm (+/- 0.05mm)
Width	12mm (+/- 1mm)
Length	10m (+/- 0.1m)

PERFORMANCE PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Peel Adhesion to steel	900 N/M	PSTC 101	over 24hr
Shear Adhesion to steel	50 hr	PSTC 107	1kg; 25mm x 25mm
Service Temperature	-40°C to 140°C		
Application Temperature	5°C to 50°C		



Optima Products, Newberry House, Michigan Drive, Tongwell, Milton Keynes, Buckinghamshire, MK15 8HQ
Tel: 01908 611117 Email: Optimaproducts@LKQCoatings.com