

Optima Sanding Belts Technical Data Sheet

optima

PRODUCT DESCRIPTION

The Optima Sanding Belt is a premium performance narrow file belt. Perfect for sanding all hard to reach and awkward metal parts. Ideal for flatting back weld points, rust removal and sanding panels back to bare metal. Cloth backing provides flexibility and extended belt life.

INSTRUCTIONS FOR USE

- Always wear the relevant PPE safety equipment including gloves, grinding apron and safety glasses
- Always ensure you use the right size belt sander, and avoid over tightening sanding belt
- Ensure you follow the belt sander manufacturer operation instructions on setting up and use
- Do not use in flamable areas

PRODUCT HIGHLIGHTS

- Strong polyester cloth backing
- High resistance to tearing
- Good flexibility to prolong life of belt
- Ceramic, aluminium oxide blend provides fast cutting and gives an even finish
- High strength join to minimise risk of snapping
- Cool Cutting Temperature
- High removal rate of metals and paint
- · Excellent cut rate at low and medium pressure

PRODUCT DETAILS

Size: 10x330mm / 20x520mm Grit: P40, P60 & P80

TECHNICAL SPECIFICATIONS

Bonding	Phenolic resin bond
Grain	Ceramic/aluminium oxide blend
Colour	Green
Backing	X-weight polyester cloth
Backing	

DISCLAIMER

All statements, technical information and recommendations are based on tests we believe to be reliable but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.



Optima Products, Newberry House, Michigan Drive, Tongwell, Milton Keynes, Buckinghamshire, MK15 8HQ **Tel:** 01908 611117 **Email:** Optimaproducts@LKQCoatings.com