



# OPT.UFR

## Ultra Flex Roll

## Technical Data Sheet

# optima

### PRODUCT DESCRIPTION

The Optima Ultra Flex Roll is a three-dimensional product that produces a dense scratch pattern with a rapid result. Suitable for both dry and wet sanding, it features an open and flexible structure and strengthened fibres which make it strong and long-lasting.

### INSTRUCTIONS FOR USE

- Always store the product in a dry environment, ideally 10°C to 25°C
- Always wear the relevant PPE safety equipment
- Tear or cut off the required amount to abrade the panel being processed
- Can be used wet with a water applicator and matting pastes if required

### PRODUCT HIGHLIGHTS

- Ultra flex roll has excellent sanding properties and long lasting durability.
- Excellent for accessing the difficult/awkward areas

### PRODUCT DETAILS

Sizes Available:	115mm x 10m
Grits:	Red (Very Fine) – P360, Grey (Ultra Fine) – P1500

### TECHNICAL SPECIFICATIONS

Bonding:	Resin
Grain:	Aluminium oxide (Very Fine)/ Silicon carbide (Ultra Fine)
Coating:	Three-dimensional
Colour:	Red & Grey
Grit Range:	P360 & P1500
Backing:	Non-Woven

### DISCLAIMER

All statements, technical information and recommendations are based on tests we believe to be reliable but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.

